

DUNLOP Building Product Information Sheet: Silicones & Butynol Sealant

	,
Product name:	DUNLOP Butynol Sealant and DUNLOP Silicones
Product line (the product line from which the product is customised)	Tiling (Silicones) and DUNLOP Butynol accessory
Product description and its intended use (measurements, materials, usage)	DUNLOP Butynol Sealant – A multipurpose construction sealant and adhesive DUNLOP Silicone – an acetic cure silicone sealant
Product identifier (if applicable):	38788 – DUNLOP Magellan Grey Silicone 310ml 24373 – DUNLOP Silicone Charred Ash 310ml 24375 – DUNLOP Silicone Havana 310ml 24376 – DUNLOP Silicone Midnight 310ml 24377 – DUNLOP Silicone Misty Grey 310ml 24378 – DUNLOP Silicone Slate Grey 310ml 24379 – DUNLOP Silicone Travertine 310ml 24380 – DUNLOP Silicone Ultra White 310ml 38873 – DUNLOP ST Silicone Clear 310ml 38872 – DUNLOP ST Silicone UltraWhite 310ml
Place of	Overseas
manufacture:	Overseas
Legal and trading name of the manufacturer(s):	ARDEX AUSTRALIA
Legal and trading name of the importer	ARDEX New Zealand Ltd
Address for	15 Alfred Street, Onehunga
service:	Auckland New Zealand 1061
Website:	Dunloptrade.co.nz
Email address	info@ardexnz.com
Phone No	0800 227 339
NZBN	9429037589653
Relevant Building	B2 DURABILITY Performance B2.3.1 & B2.3.2
Code clauses:	E2 EXTERNAL MOISTURE (Contributes) Performance E2.3.2, E2.3.3 E3 INTERNAL MOISTURE (Contributes) Performance E3.3.3, E3.3.4, E3.3.5, E3.3.6 F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1
Statement on how the building product is expected to	B2 – Products have been tested and comply with the requirements of ISO 11600 Type F 25LM



contribute to	
compliance:	Performance E2.3.2. When used as part of the tiling system, Dunlop Sealants will contribute to meeting this requirement
	Performance E3.3.3, E3.3.4, E3.3.5 and E3.3.6. When used as part of the substrate lining or finishing system, Dunlop sealants will contribute to meeting these requirements.
	F2 – Dunlop sealants have been tested for VOC and fulfil this requirement.
	Please refer to the datasheet at ardex.co.nz ARDEX SE should not be used with natural stone tiles.
requirements that would	Dunlop Butynol sealant is a multiuse construction adhesive and Sealant typically used for sealing membranes into chases and small tile repairs. Dunlop sealants are used as part of the Dunlop Tiling systems for finishing movement joints and sealing perimeter of the Tiling.
Installation requirements:	Please refer to the datasheet at dunloptrade.co.nz
	General Cleaning and maintenance should be carried out as part of normal household duties.
Is the building product/building product line subject to warning or ban under section 26?:	No
	DUNLOP BPIRS Silicones and Butynol Sealant v1.20.11.23