

DUNLOP Building Product Information Sheet: Tile Adhesives

Product name:	DUNLOP Tile Adhesives
Product line (the product line from which the product is customised)	Tiling adhesives
Product description and its intended use (measurements, materials, usage)	<p>Tile adhesives covered by this BPIS are:</p> <p>DUNLOP Super tileset DUNLOP Multipurpose Mastic DUNLOP Wall & Floor tile adhesive DUNLOP Trade resaflex DUNLOP universal tile adhesive DUNLOP Floor tile adhesive DUNLOP Floor fix</p> <p>DUNLOP Premixed resaflex DUNLOP Wall tile adhesive DUNLOP Tile and Grout</p>
Product identifier (if applicable):	<p>10360 - DUNLOP Super tileset, 20kg 10361 - DUNLOP Super tileset, 5kg 12875 - DUNLOP Multipurpose Mastic, 20kg 22004 - DUNLOP Multipurpose Mastic, 5kg 10378 - DUNLOP Wall & Floor tile adhesive, 2kg 10379 - DUNLOP Wall & Floor tile adhesive, 8kg 16552 - DUNLOP Trade resaflex, 20kg 22005 - DUNLOP Trade resaflex, 5kg 22056 - DUNLOP universal tile adhesive, 20kg 10313 - DUNLOP Floor tile adhesive, 4kg 10314 - DUNLOP Floor fix, 15kg</p> <p>10345 - DUNLOP Premixed resaflex, 1kg 10346 - DUNLOP Premixed resaflex, 4kg 38317 - DUNLOP Premixed resaflex, 15kg 38314 - DUNLOP Wall tile adhesive, 15kg 10375 - DUNLOP Wall tile adhesive, 5.5kg 10376 - DUNLOP Wall tile adhesive, 750g 13388 - DUNLOP Tile and Grout, 250g</p>
Place of manufacture:	Overseas
Legal and trading name of the manufacturer(s):	ARDEX Australia Pty
Legal and trading name of the importer	ARDEX New Zealand Ltd

Address for service:	15 Alfred Street, Onehunga Auckland New Zealand 1061
Website:	Dunloptrade.co.nz
Email address	info@ardexnz.com
Phone No	0800 227 339
NZBN	9429037589653
Relevant Building Code clauses:	Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years. (Contributes) Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.
Statement on how the building product is expected to contribute to compliance:	Clause B2 DURABILITY: Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years. Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. ARDEX Tile Adhesives are used as a tile adhesive under ceramic tiles, porcelain, fully vitrified and natural stones. ARDEX Tile adhesives are tested to comply with ISO 13007 Ceramic tiles — Grouts and adhesives — Part 1: Terms, definitions and specifications for adhesives.
Limitations on the use of the building product:	Must be installed in accordance with the technical datasheet- Substrate limitation and tile types may apply. Should not be used on floors with a deflection greater than the joist span divided by 360. Joist span must comply with NZS3604. Tiles larger than 400mm X 400mm may require reduced deflection criteria. Dimensional instability in natural stone ranges is often difficult to detect visually and may require thermal and moisture stability testing to ensure that adhesive recommendations are suitable. Do not use in layers thicker than 10mm.
Design requirements that would support the use of the building product:	DUNLOP Tile Adhesives are used as a tile adhesive in Tiling situations. Some DUNLOP Tile Adhesives may be used over some DUNLOP Undertile Waterproofing and Acoustic Systems. DUNLOP Universal tile adhesive is suitable for use in swimming pool applications
Installation requirements:	Refer to the Dunlop Tile Adhesive Datasheet for mixing instructions All Tiling work must be completed in accordance with the data sheet, BRANZ Best Practice Tiling guide and AS 3958.1
Maintenance requirements:	No maintenance is expected during the service life of the top floor covering.
Is the building product/building product line subject to warning or ban under section 26?:	No



	DUNLOP BPIS Tile Adhesives v1.17.11.23