



ARDIT RAPIDSET REPAIR MORTAR

DUNLOP ARDIT RAPIDSET REPAIR MORTAR is an extremely rapid hardening construction mortar which is trafficable after just 45 minutes and ready for floor coverings after 1 hour. Ideal for filling cracks and holes over a variety of surfaces, it is also suitable for use internally around doors, windows and plumbing installations up to a thickness of 20mm. Ideal for ramping from a feather edge to normal screed thicknesses.

APPLICATION RANGE

Suitable for repairing holes and cracks up to a depth of 20mm on the following surfaces: Concrete, Render, Screeds, Masonry, Plasterboard, Timber and Fibre-Cement Sheet. If DUNLOP ARDIT RAPIDSET REPAIR MORTAR is to be used as a wear surface, a suitable covering or coating is required. This product is to be used as a repair mortar only. If a self-levelling cementitious material is required, use DUNLOP ARDIT FLOOR LEVELLER or DUNLOP TIMBER FLOOR LEVELLER.

SURFACE PREPARATION

Surfaces must be solid, clean and free of wax, grease and all loose contaminating materials or coatings. Porous surfaces will not require priming. Direct to earth sub-floors, must be sealed with DUNLOP DAMP-PROOF prior to application.

MIXING RATIO

IMPORTANT: The mixed material is only usable for up to 15 minutes depending on ambient temperature so ensure that the surface is prepared for immediate application.

5kg Pail:

Use a clean bucket for mixing. For repairs mix 1.5L of clean water with 5kg of DUNLOP RAPIDSET REPAIR MORTAR. For ramping mix 1.3L of clean water with 5kg of DUNLOP RAPIDSET REPAIR MORTAR.

10kg Pail:

Use a clean bucket for mixing. For repairs mix 3L of clean water with 10kg of DUNLOP ARDIT RAPIDSET REPAIR MORTAR. For ramping mix 2.6L of clean water with 10kg of DUNLOP ARDIT RAPIDSET REPAIR MORTAR.

Mix to a smooth consistency, preferably using an electric mixing paddle. Only mix enough material that can be used within the 15 minute pot life.

APPLICATION

Use a trowel to apply the DUNLOP ARDIT RAPIDSET REPAIR MORTAR to the surface and immediately smooth off. After approximately 15 minutes, trim off excess material and finish off with a wet trowel and use a sponge to eliminate trowel marks and obtain a smoother surface.

DRYING TIME

DUNLOP ARDIT RAPIDSET REPAIR MORTAR will set in approximately 45 minutes after which it can be walked on. Drying will take longer at lower temperatures or in high relative humidity. Floor coverings such as vinyl, carpet and

tiles can be installed after 1 hour. High temperatures will accelerate the drying time whilst low temperatures will slow the hardening process.

COVERAGE

5kg of DUNLOP RAPIDSET REPAIR MORTAR will cover approximately 3m² at 1mm thickness or 1m² at 3mm thickness.

10kg of DUNLOP ARDIT RAPIDSET REPAIR MORTAR will cover approximately 6m² at 1mm thickness or 2m² at 3mm thickness.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in original unopened packaging in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

Do not apply in temperatures below 10°C or above 35°C. Low temperatures will extend the drying time of the mortar whilst high temperatures will shorten the pot life and drying time of the DUNLOP RAPIDSET REPAIR MORTAR.

It is not suitable for use as a wear surface without a suitable coating or floor covering such as ceramic tiles, vinyl, carpet or suitable paint. Not suitable for use in permanently wet areas.

Before any substrate preparation, installation or finishing methods relating to Dunlop products are undertaken, please be aware of any potential risks and use appropriate PPE (personal protective equipment). This may involve contacting substrate manufacturers for Safety Data Sheets.

SAFETY DATA

This product causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects. May cause cancer. May cause damage to organs through prolonged or repeated exposure. Do not breathe dust/fume. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER/doctor/physician/first aider. IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF



ARDIT RAPIDSET REPAIR MORTAR

INHALED: Remove person to fresh air and keep comfortable for breathing. Store locked up. Check with your local Council regarding disposal of contents. Keep out of the reach of children. At times updates can occur to data, for additional information and the most current technical and safety information please consult the latest Safety Data Sheet (SDS) and Technical Data Sheet found on the product page of dunloptrade.com.au.

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (Address: 2 Buda Way, Kemps Creek NSW 2178; Phone: 1800 222 841; Email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our

products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in December 2025 and is valid for 3 years, unless updated sooner. Always refer to dunloptrade.com.au for the latest technical data from ARDEX Australia Pty Ltd.

ARDEX Australia Pty Ltd
2 Buda Way, Kemps Creek NSW 2178
Phone: 1300 788 780 | Technical Support: 1800 222 841
dunloptrade.com.au

DUNLOP DRYMIX Ltd
7-9 Awa Street, Feilding 4702, New Zealand
Phone: 0800 227 339 | Technical Support: 0800 224 070
dunloptrade.co.nz