



CONCRETE RESURFACER SEALER



DUNLOP CONCRETE RESURFACER SEALER is a clear durable and hard wearing semi-gloss “wet look” sealer that protects and enhances concrete floor surfaces such as a newly applied DUNLOP CONCRETE RESURFACER and old concrete surfaces. This sealer can be tinted to a range of popular colours.

COLOUR SELECTION

This sealer can be used as a clear sealer or be tinted with the DUNLOP RESURFACER SEALER TINT.

SUITABLE SURFACES

Apply over newly applied DUNLOP CONCRETE RESURFACER, existing concrete or previously sealed concrete to provide a uniform appearance.

SURFACE PREPARATION

Existing concrete: All concrete substrates must be structurally sound, solid, thoroughly clean and free of any release agents, paints, concrete laitance, patching compounds, dust, dirt, oils and any other contaminant that could act as a bond breaker. If necessary, mechanically prepare the floor to sound, solid concrete by shot blasting, grinding or similar. High-pressure (5000 psi) power washing may also be used to remove dust, dirt and debris, though the concrete must then be allowed to dry thoroughly before proceeding.

Acid etching, adhesive removers, solvents and sweeping compounds are not acceptable means of cleaning the substrate. The use of sanding equipment is not an effective method to remove curing and sealing compounds. Use a lawn edger to clean around walkways, paths or driveways, as well as around planter boxes and landscaped areas. Substrates must be dry for a successful application.

Resurfaced concrete: After application of the DUNLOP CONCRETE RESURFACER, wait a minimum of 24 hours before applying the sealer.

New concrete: Allow to cure for a minimum of 4-6 weeks.

Existing concrete (unsealed): Ensure the surface is thoroughly clean and dry as per Surface Preparation. Previously sealed concrete (solvent or water-based sealers): ensure the surface is thoroughly clean and dry as per Surface Preparation. Test the sealer in small inconspicuous areas to determine suitability (penetration and adhesion).

APPLICATION AS A CLEAR OR TINABLE SEALER

1. Should a coloured or tinted sealer be preferred, select the desired tint. Pour the entire contents of the DUNLOP CONCRETE RESURFACER SEALER TINT (200ml) into this Sealer (3.8L).
2. Stir well before and during use with a broad paddle or lightly shake the sealed container. The product is supplied

ready for use, so no thinning is required.

3. Pour into a paint tray and apply by brush, lambswool roller or a low volume spray applicator.

Do not pour the sealer directly onto the surface when applying by brush or roller. When spraying, back rolling is recommended to prevent puddles or ponding. The first coat is considered as a primer or key coat. Apply a minimum of 2 even coats; apply the second coat at right angles for best results and finish with long even strokes in the same direction. Additional coats can be applied depending on preference, wear and desired gloss level.

DRYING & RECOATING

Touch dry in a minimum of 2 hours and recoat once the product is touch dry. After application of final coat allow a minimum of 3 hours before subjecting to foot traffic and allow a minimum of 24 hours before subjecting to vehicle traffic. Drying times will vary in cold or humid conditions.

Do not apply if windy or the surface and air temperature is under 10°C or over 35°C or if freezing temperatures could occur within 24 hours.

COVERAGE

This product will cover approximately 8-10m² per litre, depending on surface texture or porosity.

CLEAN UP

Clean all equipment in Xylene immediately on completion of project.

SHELF LIFE

12 months when stored in a dry place in the original unopened packaging, at 23°C and 50% relative humidity.

PRECAUTIONS

This sealer is flammable please refer to Safety Data. This sealer is not intended for areas with heavy traffic. Do not use in any area that will be permanently submerged. The sealer will not waterproof the surface being sealed. This sealer is not recommended for use on smooth surfaces around swimming pools or wet areas unless the surface is textured for non-slip. Not being suitable for tiled surfaces such as porcelain or impervious surfaces.

Should a non-slip surface be required the application of washed river sand can be broadcasted or sprinkled evenly over the wet sealer, followed by a second coat of sealer once the first coat has dried.



CONCRETE RESURFACER SEALER

Avoid sealing driveways and paths during the heat of the day, as this may prevent penetration and adhesion of this product. Avoid sealing when dew or rain is likely.

This sealer will repel stains from spills that are cleaned up immediately. If a stain is left in place for an extended period the sealer's ability to repel the stain is reduced. If this sealer is tinted using the DUNLOP CONCRETE RESURFACER SEALER TINT it is non-refundable, so choose your colour carefully. If the sealer has tint added, check that the colour is suitable for your requirements before it is applied. For best results and colour consistency, multiple cans of tinted product should be combined and thoroughly mixed together before starting to ensure colour uniformity.

SAFETY DATA

Flammable liquid and vapour. Harmful when in contact with skin and if inhaled. Causes eye and skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Ensure adequate ventilation during use. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell or if swallowed. Do not induce vomiting. In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Keep out of the reach of children. Check with your local Council regarding the disposal of contents and packaging. Additional information is in the Safety Data Sheet SDS at www.dunlopdiy.com.

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (Address: 7/20 Powers Road Seven Hills NSW 2147; Phone: 1800 222 841; Email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in June 2020 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopdiy.com for the latest technical data from ARDEX Australia Pty. Ltd.