



MULTIPURPOSE TILE ADHESIVE



CERAMIC,
PORCELAIN,
MOSAIC



WALL &
FLOOR



GROUT TIME



INDOOR &
OUTDOOR



STANDARD



YIELD - PER BAG
6MM TROWEL



**Available in:
5KG & 20KG Bags**

Multipurpose Tile Adhesive is a poly-modified tile adhesive for internal wall and floor use. It provides strong, flexible bonding for ceramic, porcelain, and natural stone tiles—including large formats.

KEY ADVANTAGES

- Strong, flexible bond ideal for walls and floors
- Excellent slip resistance for secure tile placement
- Extended open time for easy adjustments
- Suitable for large-format tiles and wet areas

TYPICAL USES

- Wall and floor tiling in bathrooms, kitchens, and laundries
- Large-format tile installations – ideal for heavier tiles that need extra grip
- Tiling over concrete surfaces – great for interior renovations and high-use spaces

STANDARDS

- Complies with C2TE-S1

HOW TO USE:

- Clean the repair area – Remove any dust, loose material, oil, or contaminants.
- Getting Ready – Use NZS 3114 standards and a notched trowel (6mm for walls, 10mm for floors) to apply adhesive.

- Spread Dunlop Multipurpose Tile Adhesive 3–10mm thick and press tiles in firmly, ensuring full contact.
- Wait 24 hours before grouting, allowing extra time in cool or damp conditions.

PRODUCT LIMITATIONS

- Not suitable for continuous water immersion (e.g. pools), metal surfaces, or unstable substrates like timber. For moisture-sensitive natural stone, seek specialist advice or use recommended systems.



Scan to visit
our site

0800 224 070





MULTIPURPOSE TILE ADHESIVE

TECHNICAL DATA

Size	5kg & 20kg
Appearance	Grey
Shelf Life	12 months
Application Temp	5°C - 30°C
Water content per bag	6-6.5L per 20kg
Open Time	30 mins
Adjustment Time	20 mins
Grout Time	24 hours
Pot Life	3 hours
Classification	C2TE-S1
Safety Information	Refer to the Safety Data Sheet on our website

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, Dunlop Drymix Ltd. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of DUNLOP DRYMIX LTD. For all advice concerning the use or suitability of this product for a particular application, please contact DUNLOP DRYMIX LTD. If this product is defective, please contact the merchant the material was purchased from or DUNLOP DRYMIX LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act

November 2025



Scan to visit
our site

0800 224 070

