

# PATCH PRO

## COLD MIX ASPHALT



NO MIXING OR  
WATER  
REQUIRED



USE IN ALL  
WEATHER  
CONDITIONS



TRAFFIC READY  
IMMEDIATELY



**Available in:  
20kg Bags**

Dunlop Patch Pro Asphalt is a ready-to-use for fast, durable repairs to driveways, roads and pathways. No mixing or heating is required—just apply, compact and go. Designed to bond strongly the mix is smooth and less crumbly than traditional cold mix asphalts, it withstands traffic, weather, and everyday wear.

### KEY ADVANTAGES

- Fast-setting and easy to apply
- Durable and long-lasting repair
- Excellent adhesion to existing asphalt
- Can be trafficked soon after application
- Performs in all New Zealand weather conditions

### TYPICAL USES

- Driveways and residential car parks
- Footpaths, walkways, and garden paths
- Potholes, surface cracks, and worn areas on roads and streets
- Uneven or damaged areas around kerbs and edges

### HOW TO USE:

1. **Prepare:** Clear loose debris, dirt and broken asphalt from the repair area
2. **Apply:** Pour Patch Pro into the hole or crack, slightly overfilling
3. **Compact:** Firmly tamp or roll to level with the surrounding surface
4. **Ready:** Light foot traffic immediately, vehicle traffic once fully compacted

### PRODUCT LIMITATIONS

- Not intended for full depth road reconstruction or large scale industrial pavements
- Apply to areas free of standing water and compact in temperatures between 5-30°C
- Very deep potholes should be filled in layers, approx. 50-75mm, compacting each layer
- Although traffic ready immediately, extremely heavy or continuous loads in the first 24-48 hours may affect long-term finish



Scan to visit  
our site

0800 224 070



# PATCH PRO

## COLD MIX ASPHALT

### TECHNICAL DATA

<b>Size</b>	20kg
<b>Shelf Life</b>	12 months
<b>Coverage</b>	Approximately 0.0012m <sup>3</sup> per 20kg bag
<b>Application Temperature</b>	5–30 °C
<b>Safety Information</b>	Refer to the Safety Data Sheet on our website

#### DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, Dunlop Drymix Ltd. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of DUNLOP DRYMIX LTD. For all advice concerning the use or suitability of this product for a particular application, please contact DUNLOP DRYMIX LTD. If this product is defective, please contact the merchant the material was purchased from or DUNLOP DRYMIX LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act

March 2026



Scan to visit  
our site

0800 224 070

