



READY-TO-GO TILE & GROUT

DUNLOP READY-TO-GO TILE & GROUT is an ideal repair product featuring easy application with no mixing and no mess. A tile adhesive and grout in one, it is suitable for wall tiles and mosaics for indoor and outdoor tiling projects.

SURFACE PREPARATION

Suitable for concrete, cement render, fibre cement sheet, plasterboard and prepared painted surfaces. Surfaces must be consistently flat and firmly fixed. Clean off dust, oil, grease and all loose contaminating materials or coatings. Ensure surfaces are dry, with no residue or permanent dampness. Prime all surfaces with DUNLOP PRIMER & ADDITIVE and allow to dry.

CEMENT RENDER

Allow to cure for 7 days. Render should have a wood float finish.

PLASTERBOARD

There is no need to prime the cardboard surface. However, where sheets are joined, DUNLOP PRIMER & ADDITIVE must be used over the base jointing compound. Do not use the topping compound in areas which are to be tiled.

FIBRE-CEMENT SHEET

Remove surface dust with a damp sponge and prime with DUNLOP PRIMER & ADDITIVE and allow to dry before tiling.

PAINTED SURFACES

Oil-based paint should be roughened mechanically and loose flaking paint should be removed. Ensure the paint is suitable for tiling over. Thoroughly remove water-based paints. Do not use paint stripper or solvents. Allow surface to dry after cleaning.

TILE TYPES

Wall tiles including ceramic, porcelain, marble (excluding moisture sensitive stone).

TILING INSTRUCTIONS

1. Use a 4.5mm to 6mm notched trowel to spread adhesive achieving a minimum 1mm bed thickness. If tiles are dusty clean with a damp sponge.
2. Press and slide the tile into position ensuring the whole of the back of the tile is in good contact with the adhesive.
3. Adjustment of tiles should be carried out within 60 minutes of laying (at 23°C, 50% humidity).
4. Press tiles into adhesive/grout bed until excess grout flows into grout joints. Apply extra material into grout joints and follow grouting instructions below.
5. When tiling with DUNLOP TILE & GROUT, the joints can be grouted immediately.

GROUTING INSTRUCTIONS

1. Prior to grouting, it is advisable to check ease of cleaning

with tiles that have a textured or matt surface.

2. Squeeze grout firmly into grout joints. Ensure the grout is compacted firmly into the joints by using a grout float or squeegee. Minimise excess grout on the tile surface by scraping with a Grout float or squeegee.

3. Allow grout to firm up in joint for approx 15 minutes and remove any excess grout from the surface of the tile with a dense, damp, small-pored sponge. Rinse sponge frequently.

4. When grout has hardened in the joint (approx 6-24 hrs) buff and polish tile surface with a clean dry cloth.

5. When grouting outdoors it is essential to protect the grouted areas from all extremes of climate for 7 days.

PRECAUTION

The tile adhesive is not suitable for use over Dunlop Waterproofing membrane or in wet areas such as a shower recess. Not suitable for use in immersed conditions. Do not use grout in expansion or movement joints.

SAFETY DATA

This product causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. Avoid breathing mist/vapors/spray. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Immediately call a POISON CENTER/doctor/physician/first aider. **IF ON SKIN:** Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Store locked up. Check with your local Council regarding disposal of contents. At times updates can occur to data, for additional information and the most current technical and safety information please consult the latest Safety Data Sheet (SDS) and Technical Data Sheet found on the product page of dunloptrade.com.au.

10 YEAR GAUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of



READY-TO-GO TILE & GROUT

this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (Address: 2 Buda Way, Kemps Creek NSW 2178; Phone: 1800 222 841; Email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in December 2025 and is valid for 3 years, unless updated sooner. Always refer to dunloptrade.com.au for the latest technical data from ARDEX Australia Pty

Ltd.

ARDEX Australia Pty Ltd
2 Buda Way, Kemps Creek NSW 2178
Phone: 1300 788 780 | Technical Support: 1800 222 841
dunloptrade.com.au

DUNLOP DRYMIX Ltd
7-9 Awa Street, Feilding 4702, New Zealand
Phone: 0800 227 339 | Technical Support: 0800 224 070
dunloptrade.co.nz