

# SLABCRETE

## HI STRENGTH CONCRETE

**45**  
MPa

45MPa  
IN 28 DAYS

**30**  
MIN

WORK TIME

**1-2**  
HRS

SET TIME

**28**  
DAYS

FULL CURE



**Available in:**  
**20kg (2079481) Bags**

Dunlop Slabcrete is a high-strength, pre-blended concrete mix designed for heavy-duty applications requiring strength of 45MPa, it delivers a smooth, workable consistency with excellent finishability. Ideal for both DIYers and professionals needing reliable performance in structural and load-bearing projects.

### KEY ADVANTAGES

- High Strength 45MPa great for heavy duty applications
- Crack resistant with low shrinkage
- Jobs requiring high early strength such as in colder weather or post work

### TYPICAL USES

- Slabs for sheds, patios and outdoor living areas
- Paths and heavy traffic areas
- Footings and retaining walls – great for landscape work

### HOW TO USE:

- Clean the repair area – Remove any dust, loose material, oil, or contaminants.
- Mix with clean water – Add 1.7-2L of water gradually to the powder and mix to a smooth, consistent mix.
- Pour the mix – Use a rake or spade to evenly spread the product to reach all corners.
- Remove any air pockets – Tap the box every 1 - 2m, a mechanical concrete vibrator is recommended.
- Allow to cure – Protect the area from foot traffic, vehicles and moisture for at least 7 days.

### PRODUCT LIMITATIONS

- Too much water can weaken the concrete mix and reduce the strength.
- Due to high cement content this mix may feel different to traditional lower MPA mixes.
- Whilst Dunlop Drymix Slabcrete is designed for high strength commercial and civil applications, it is always recommended to seek site specific advice before use.



Scan to visit  
our site

0800 224 070

# SLABCRETE

## HI STRENGTH CONCRETE

### TECHNICAL DATA

<b>Size</b>	20kg
<b>Shelf Life</b>	12 months
<b>Strength</b>	45Mpa at 28days
<b>Water Ratio</b>	1.7 - 2L per 20kg bag
<b>Mixing Time</b>	6 mins
<b>Work Time</b>	30 mins
<b>Initial Set Time</b>	1 - 2 hours
<b>Final cure</b>	28 days
<b>Safety Information</b>	Refer to the Safety Data Sheet on our website

#### DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, Dunlop Drymix Ltd. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of DUNLOP DRYMIX LTD. For all advice concerning the use or suitability of this product for a particular application, please contact DUNLOP DRYMIX LTD. If this product is defective, please contact the merchant the material was purchased from or DUNLOP DRYMIX LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act

