

# Dunlop Ardit Floor Leveller Ardex (Ardex Australia)

Chemwatch: 22-5921 Version No: 4.1.1.1 Safety Data Sheet according to WHS and ADG requirements

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Dunlop Ardit Floor Leveller
Synonyms	Not Available
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Levelling of uneven concrete surfaces prior to the application of floor coverings.

#### Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex Australia)
Address	20 Powers Road Seven Hills NSW 2147 Australia
Telephone	1800 224 070
Fax	1300 780 102
Website	Not Available
Email	Not Available

#### Emergency telephone number

Association / Organisation	Ardex (Ardex Australia)
Emergency telephone numbers	1800 224 070 (Mon-Fri, 9am-5pm)
Other emergency telephone numbers	Not Available

## **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

## HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

	Min	Max	
Flammability	0		
Toxicity	1 📕		0 = Minimum
Body Contact	3	1	1 = Low
Reactivity	0		2 = Moderate
Chronic	2	1	3 = High 4 = Extreme

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements

Hazard pictogram(s)



Issue Date: 01/11/2019

Print Date: 04/11/2020

S.GHS.AUS.EN

Signal word	Danger
Hazard statement(s)	
H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

### Precautionary statement(s) Prevention

-		
P	P271	Use only outdoors or in a well-ventilated area.
P	P280	Wear protective gloves/protective clothing/eye protection/face protection.
P	P261	Avoid breathing dust/fumes.
P	P272	Contaminated work clothing should not be allowed out of the workplace.

## Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER or doctor/physician.	
P321	Specific treatment (see advice on this label).	
P362	Take off contaminated clothing and wash before reuse.	

## Precautionary statement(s) Storage

	-	
P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

## Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
14808-60-7.	30-60	graded sand
65997-15-1	10-30	portland cement
471-34-1	10-30	calcium carbonate
65997-16-2	10-30	calcium aluminate cement
7778-18-9	<10	calcium sulfate
Not Available	<10	additives, unregulated

#### **SECTION 4 First aid measures**

## Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Firefighting measures**

#### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

## Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>Decomposition may produce toxic fumes of: sulfur oxides (SOx) silicon dioxide (SiO2) metal oxides</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	Not Applicable

#### SECTION 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures

See section 8

#### Environmental precautions

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	Moderate hazard.  CAUTION: Advise personnel in area.  Alert Emergency Services and tell them location and nature of hazard.  Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

#### Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

#### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>	
Storage incompatibility	<ul> <li>WARNING: Avoid or control reaction with peroxides. All <i>transition metal</i> peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.</li> <li>The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.</li> <li>Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.</li> <li>Avoid contact with copper, aluminium and their alloys.</li> </ul>	

### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits (OEL)

Source	Ingredient	Material name	TWA	STEL	Pea	k	Notes	
Australia Exposure Standards	graded sand	Silica - Crystalline: Quartz (respirable dust)	0.05 mg/m3	Not Available	Not Ava	lable	Not Available	
Australia Exposure Standards	portland cement	Portland cement	10 mg/m3	Not Available	Not Ava	lable	(a) This value is for inhalable dust contain asbestos and < 1% crystalline silica.	
Australia Exposure Standards	calcium carbonate	Calcium carbonate	10 mg/m3	Not Available	Not Ava	lable	(a) This value is for inhalable dust cont asbestos and < 1% crystalline silica.	
Australia Exposure Standards	calcium sulfate	Calcium sulphate	10 mg/m3	Not Available	Not Ava	lable	(a) This value is for asbestos and < 1%	inhalable dust containing n crystalline silica.
Emergency Limits								
Ingredient	Material name			TE	EL-1		TEEL-2	TEEL-3
graded sand	Silica, crystallin				75 mg/m3		33 mg/m3	200 mg/m3
calcium carbonate	Carbonic acid, o	alcium salt		45 ו	mg/m3		210 mg/m3	1,300 mg/m3
Ingredient	Original IDLH					Revised		
graded sand	25 mg/m3 / 50 r	na/m3				Not Avai		
portland cement	5,000 mg/m3	iig/iii3				Not Avai		
calcium carbonate	Not Available					Not Avai		
calcium aluminate cement	Not Available							
	Not Available					Not Avai		
calcium sulfate	NOL AVAIIADIE					NOL AVAI	lable	
Occupational Exposure Banding	-				-			
Ingredient					mal Exposure Band Limit			
xposure controls		outcomes associated with expos re concentrations that are expe						
Appropriate engineering controls	be highly effecti The basic types Process control Enclosure and/o	trols are used to remove a haza ve in protecting workers and will of engineering controls are: s which involve changing the wa r isolation of emission source w	typically be in y a job activity hich keeps a s	dependent o	of worker in is done to r	teractions t	o provide this high le	evel of protection.
	auus anu ren	oves" air in the work environme	nt.					
Personal protection		oves' air in the work environme	nt.					
Personal protection Eye and face protection	Safety glass     Chemical g     Contact len	ses with side shields.	soft contact le				irritants. A written p	olicy document, describing
	Safety glass     Chemical g     Contact len	ses with side shields. bggles. ses may pose a special hazard; of lenses or restrictions on use,	soft contact le				irritants. A written p	olicy document, describing

Personal hygiene is a key element or effective hand care.
Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.
Polychloroprene.
nitrile rubber.

polychloroprene.
nitrile rubber.
butyl rubber.

 Body protection
 See Other protection below

 Other protection

 • Overalls.
 • P.V.C apron.
 • Barrier cream.
 • Skin cleansing cream.
 • Skin cleansing

#### **Respiratory protection**

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor         Half-Face Respirator         Full-Face Respirator         Powered Air Respirator	
---	--

up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

• Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

## **SECTION 9** Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Grey powder; insoluble in water. Loose Bulk Density: 1.3 approx.			
Physical state	Divided Solid	Relative density (Water = 1)	2.6 approx.	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable	
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	Not Applicable	Taste	Not Available	
Evaporation rate	Not Applicable	Explosive properties	Not Available	
Flammability	Not Applicable	Oxidising properties	Not Available	
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable	
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable	
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available	
Solubility in water	Immiscible	pH as a solution (1%)	Not Available	
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available	

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 Toxicological information**

#### Information on toxicological effects

information on toxicological e	
Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Effects on lungs are significantly enhanced in the presence of respirable particles.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.

Skin Contact	The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation. Sensitisation is due to soluble chromates (chromate compounds) present in trace amounts in some cements and cement products. Soluble chromates readily penetrate intact skin. Cement dermatitis can be characterised by fissures, eczematous rash, dystrophic nails, and dry skin; acute contact with highly alkaline mixtures may cause localised necrosis. Overexposure to the breathable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity and chest infections. Repeated exposures in the workplace to high levels of fine-divided dusts may produce a condition known as pneumoconiosis, which is the lodgement of any inhaled dusts in the lung, irrespective of the effect. This is particularly true when a significant number of particles less than 0.5 microns (1/50000 inch) are present.

	ΤΟΧΙΟΙΤΥ	IRRITATION		
Dunlop Ardit Floor Leveller	Not Available	Not Available		
	ΤΟΧΙΟΙΤΥ	IRRITATION		
	0.3 mg/kg <sup>[2]</sup>	Not Available		
graded sand	50 mg/kg <sup>[2]</sup>			
	Oral (rat) LD50: =500 mg/kg <sup>[2]</sup>			
	ΤΟΧΙΟΙΤΥ	IRRITATION		
portland cement	Not Available	Not Available		
	ΤΟΧΙΟΙΤΥ	IRRITATION		
	Oral (rat) LD50: 6450 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.75 mg/24h - SEVERE		
calcium carbonate		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>		
		Skin (rabbit): 500 mg/24h-moderate		
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>		
	ΤΟΧΙΟΙΤΥ	IRRITATION		
calcium aluminate cement	Not Available	Not Available		
	ΤΟΧΙΟΙΤΥ	IRRITATION		
	Oral (mouse) LD50: =4052-4226 mg/kg <sup>[2]</sup>	Not Available		
calcium sulfate	Oral (rat) LD50: >10000 mg/kg <sup>[2]</sup>			
	Oral (rat) LD50: >3000 mg/kg <sup>[2]</sup>			
	Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>			
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			

PORTLAND CEMENT	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.	
CALCIUM CARBONATE	No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.	
CALCIUM SULFATE	Gypsum (calcium sulfate dehydrate) irritates the skin, eye, mucous membranes, and airways. A series of studies involving Gypsum industry workers in Poland reported chronic, non-specific airways diseases. Repeat dose toxicity: Examination of workers at a gypsum manufacturing plant found restrictive defects on long-function tests in those who were chronically exposed to gypsum dust. Synergistic/antagonistic effects: Gypsum appears to be protective on quartz toxicity in animal testing.	
GRADED SAND & PORTLAND CEMENT & CALCIUM ALUMINATE CEMENT	No significant acute toxicological data identified in literature search.	
PORTLAND CEMENT & CALCIUM CARBONATE & CALCIUM ALUMINATE CEMENT & CALCIUM SULFATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.	

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	*	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
			ot available or does not fill the criteria for classification le to make classification

## **SECTION 12 Ecological information**

	Endpoint	Test Duration (hr)	Species	Value	Source
Dunlop Ardit Floor Leveller	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Source
graded sand	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Source
portland cement	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	72	Algae or other aquatic plants	Algae or other aquatic plants >14mg/L	
calcium carbonate	EC10	72	Algae or other aquatic plants	Algae or other aquatic plants >14mg/L	
	NOEC	72	Algae or other aquatic plants	14mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	LC50	96	Fish	>100mg/l	. 2
calcium aluminate cement	EC50	48	Crustacea	5.4mg/L	2
	EC50	72	Algae or other aquatic plants	3.6mg/L	2
	NOEC	72	Algae or other aquatic plants	2.6mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	LC50	96	Fish	>1-970mg/L	2
calcium sulfate	EC50	72	Algae or other aquatic plants	>79mg/L	2
	EC98	720	Algae or other aquatic plants	=1872.000mg/	. 1
	NOEC	24	Crustacea	<2500.0mg/L	1

DO NOT discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil Persistence: Air			
calcium sulfate	HIGH HIGH			
Bioaccumulative potential				
Ingredient	Bioaccumulation			
calcium sulfate	LOW (LogKOW = -2.2002)			
Mobility in soil				
Ingredient	Mobility			
calcium sulfate	LOW (KOC = 6.124)			

## **SECTION 13 Disposal considerations**

Waste treatment methods	
Product / Packaging disposal	<ul> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> </ul>

Labels Required

## Dunlop Ardit Floor Leveller

	<ul> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Bury residue in an authorised landfill.</li> </ul>	
	Recycle containers if possible, or dispose of in an authorised landfill.	
SECTION 14 Transport information		

## Marine Pollutant NO HAZCHEM Not Applicable Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable **SECTION 15 Regulatory information** Safety, health and environmental regulations / legislation specific for the substance or mixture graded sand is found on the following regulatory lists Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Australian Inventory of Industrial Chemicals (AIIC) Monographs International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Chemical Footprint Project - Chemicals of High Concern List Monographs - Group 1 : Carcinogenic to humans

#### portland cement is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

calcium carbonate is found on the following regulatory lists Australian Inventory of Industrial Chemicals (AIIC)

#### calcium aluminate cement is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

calcium sulfate is found on the following regulatory lists Australian Inventory of Industrial Chemicals (AIIC)

#### **National Inventory Status**

National Inventory	Status		
Australia - AIIC	Yes		
Australia - Non-Industrial Use	No (graded sand; portland cement; calcium carbonate; calcium aluminate cement; calcium sulfate)		
Canada - DSL	Yes		
Canada - NDSL	No (graded sand; portland cement; calcium aluminate cement; calcium sulfate)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (portland cement)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	No (portland cement; calcium aluminate cement)		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (calcium aluminate cement)		
Vietnam - NCI	Yes		
Russia - ARIPS	No (calcium aluminate cement)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

#### **SECTION 16 Other information**

Revision Date	01/11/2019
Initial Date	30/11/2009

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
3.1.1.1	11/04/2016	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Classification, Disposal, Fire Fighter (fire/explosion hazard), First Aid (skin), First Aid (swallowed), Personal Protection

Version	Issue Date	Sections Updated	
		(Respirator), Personal Protection (eye), Personal Protection (hands/feet), Storage (storage incompatibility), Storage (storage requirement)	
4.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification	

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure  ${\sf Limit}_{\circ}$ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors** BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.